

	<h2>PELEMURA PASTA</h2> <h3>Ready Mixed Levelling Compound</h3>
---	---

Description

General purpose, ready mixed fine levelling compound for interior surfaces. It is suitable for levelling plastered or rendered surfaces, fair-face concrete surfaces, gypsum boards etc. It has very good working and levelling properties. It dries fast and can be easily sanded. The final smooth surface is suitable for any type of decoration.

Technical Specifications

Vehicle type	:	Styrene / Acrylic Copolymer
Weight solids	:	71.5±1%
Viscosity	:	175±5 Poise
Coverage on a smooth surface	:	~0.5–1.0 kg/m ²
Dilution	:	Not recommended, unless a more fluid consistency is required.
Drying time at 25°C and relative humidity 50%	:	Touch dry: 1 hour depending on weather conditions For deep cracks (>0.5mm) allow the first layer to dry for 12 hours, before applying a second layer
Flash point	:	Non-flammable

Instructions for Use

SURFACE PREPARATION

All surfaces should be clean, free of dust, oil, residues of other building materials, etc. before applying the product. **Pelemura Pasta** is ready for use. It can also be applied to cover capillary cracks on cement rendering surfaces.

Before decorating, the final surface should be made smooth using fine sandpaper. After sanding the surface should be primed with Peletico's **EcoPrimer**. Final surface can be decorated using emulsion paints, enamel paints, acrylic paints, etc. (all available from Peletico).

All new masonry or concrete surfaces must be cured for at least three weeks prior to painting.

APPLICATION

Thinning/Cleaning: Tap water. Thinning is not recommended unless a more fluid consistency is required.

Application tools: Spatula or paint scrapper.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use.

Cleaning of Tools: Clean tools immediately after use with hot water and soap.

PACKING: 7KG and 14KG.

COLOUR: Off White.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



Health and Safety Measures

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or label.
- It contains a biocidal product. It contains 5-Chloro-2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.

