



PELEBOND

Universal Adhesive

Description

Universal adhesive, for general use in building and construction work for interior and exterior surfaces. It can be used as a concrete and plaster additive, primer of porous surfaces in rendering and screeding.

Technical Specifications

Vehicle type	:	Vac/VeoVa/Acrylic
Specific Gravity	:	1.00±0.02
Volume solids	:	23±1%
Weight solids	:	20±1%
Viscosity	:	84±2KU's
Dilution	:	With water
Drying time at 25°C and relative humidity 50%	:	Touch dry: 2-3 hours when used as a primer, depending on weather conditions
Flash point	:	Non-flammable
EU limit value for this product (cat. A/h): 30g/l (2010). This product contains max 10g/l VOC		

Instructions for Use

SURFACE PREPARATION

Surface must be free of dust, grease, or other materials. Peeling or cracked surfaces should be scraped and sanded to a sound surface. Surfaces must be dry before applying **PELEBOND**.

USES

AS AN ADDITIVE FOR CEMENT MORTARS AND CEMENT BASED PRODUCTS

Replace the mixing water with a solution of **PELEBOND**-water 1:5 by volume.

PRIMING OF POROUS SURFACES

Apply **PELEBOND**-water 1:10 to 1:15 by volume depending on porosity of surface. Allow to dry. Repeat if necessary.

APPLICATION

Thinning/Cleaning: Tap water.

Application tools: Brush or Roller.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before and during use.

Cleaning of Tools: Tools must be cleaned immediately after use with warm water and soap.

PACKING: 0.75L, 5L and 15L.

COLOUR: White.

Health and Safety Measures

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice and show the container or label.
- If swallowed, seek medical advice immediately and show the container or label.
- It contains a biocidal product. It contains 5-Chloro-2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*