

	<p><b>PELESTIK</b></p> <p><b>Synthetic Rubber Adhesive</b></p>
---	--

### Description

Synthetic rubber adhesive, suitable for multipurpose applications for interior and exterior use. It can be used in bonding PVC, rubber, leather, cork, wood, laminated plastic, etc. It is not recommended for bonding polystyrene.

### Technical Specifications

Vehicle type	:	Rosin
Specific Gravity	:	0.825±0.025
Weight solids	:	22.5±2.5%
Viscosity	:	2000mPas, Brookfield LVT
Dilution	:	Not recommended
Drying time at 25°C and relative humidity 50%	:	10-15 minutes depending on weather conditions
Flash point	:	18°C

### Instructions for Use

#### SURFACE PREPARATION

The surfaces to be bonded must be dry and free from dust and dirt.

#### APPLICATION

**Thinning/Cleaning:** Thinner 11/11 (Peletico's product). Thinning is not recommended.

**Application tools:** Roller or Brush.

**Application Temperature:** Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before application. Apply evenly on both surfaces. Leave surfaces to dry for 10-15 minutes. For better results, press firmly using a rubber mallet, or a heavy cylinder or any other suitable tool. During the first 48 hours the bonded surfaces should not be subjected to high temperatures.

**Cleaning of Tools:** Tools must be cleaned immediately after use with Thinner 11/11 (Peletico's product).

**PACKING:** 0.25L, 0.5L, 1L and 4L.

**COLOUR:** Beige hue.

**STORAGE:** Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



## Health and Safety Measures

- Keep out of reach of children.
- Highly flammable liquid and vapour.
- Suspected of damaging fertility. Suspected of damaging the unborn child.
- May be fatal if swallowed and enters airways.
- May cause damage to organs through prolonged or repeated exposure.
- Causes serious eye irritation.
- Causes skin irritation.
- May cause an allergic skin reaction.
- May cause drowsiness or dizziness.
- Harmful to aquatic life with long lasting effects.
- Repeated exposure may cause skin dryness or cracking.
- Obtain special instructions before use.
- Keep away from heat, hot surfaces, sparks, open flames. No smoking.
- Wear protective gloves/ protective clothing/eye protection/ face protection.
- **IF SWALLOWED:** Immediately call a POISON CENTRE or doctor and show the container or label.
- **IF INHALED:** Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- **IN CASE OF FIRE:** Use Dry Powder or **Carbon dioxide** extinguisher.
- For more information please refer to Safety Data Sheet.

**Contains:** ROSIN, TOLUENE, N-HEXANE.

### WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

***Note:** The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*

