



BITUMINOUS ALUMINIUM

Bituminous Aluminium Paint

Description

A Bitumen and Hydrocarbon Resin based Aluminium paint with excellent flow properties for exterior surfaces. It is used as a decorative and protective coating over tar and bitumen based products, offering protection against ultra violet degradation. It is recommended as a protective finish for Bitumen-type roofing materials. It exhibits exceptional flexibility, durability, weather resistance, UV resistance.

Technical Specifications

Vehicle type	:	Hydrocarbon Resin
Specific Gravity	:	0.99±0.02
Weight solids	:	58±1%
Viscosity	:	40"-50" Ford cup No.4
Coverage (on a smooth surface)	:	10-12m ² /L / coat
Dilution	:	For brush or roller: up to 10%, by volume For airless spray: up to 20%, by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 4-6 hours Recoat: After 24 hours, depending on weather conditions
Flash point	:	<21°C
European Union Limit for this product (Cat. A/i): 500g/l (2010). This product contains max 400g/l VOC		

Instructions for Use

SURFACE PREPARATION

Remove all surface contamination, e.g. dust, oil stains and dampness by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Peeling or cracked paint should be scraped off and sanded to a sound surface.

APPLICATION

Thinning/Cleaning: White Spirit.

Application tools: Brush, Roller, Conventional or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before and during use. Apply two coats by brush, roller or airless spray. After application the surface has a silver aluminium colour.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with White Spirit.

PACKING: 4L, 20L.

COLOUR: Silver Aluminium.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



Health and Safety Measures

- Keep out of reach of children.
- Flammable liquid and vapour.
- Causes damage to organs, through prolonged or repeated exposure.
- May cause drowsiness or dizziness.
- Toxic to aquatic life with long lasting effects.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Wear protective gloves / eye protection / face protection.
- IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- Call a POISON CENTRE / doctor if you feel unwell and show the container or label.
- For more information please refer to Safety Data Sheet.

Contains: WHITE SPIRIT.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*

