



## PERLOTEX MATT

**Premium Quality Fine Textured and Protective Finish**

### Description

Premium quality, fine textured, decorative and protective finish for exterior surfaces. It can be applied over most exterior plastered and levelled surfaces, masonry, textured surfaces etc. It combines excellent opacity with maximum durability. It covers hairline cracks.

### Technical Specifications

Vehicle type	:	Va/VeoVa/Acrylic
Specific Gravity	:	1.37±0.03
Volume solids	:	37±1%
Weight solids	:	54±1%
Viscosity	:	102±2KU's
Gloss	:	<6 at 85° Matt (EN13300)
Coverage (on a smooth surface)	:	10-12m <sup>2</sup> /L / coat
Dilution	:	Prime coat up to 20% by volume Finishing coat up to 10% by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 1-2 hours Recoat: 4 hours depending on weather conditions
Flash point	:	Non-flammable
<b>EU limit value for this product (cat. A/c): 40g/l (2010). This product contains max 32g/l VOC</b>		

### Instructions for Use

#### SURFACE PREPARATION

Remove all surface contamination, e.g. dust, oil stains and dampness by washing with the appropriate cleaner, rinse thoroughly and allow drying. In case of efflorescence (salt exudation) clean with a hard brush. Peeling or cracked paint should be scraped off and sanded to a sound surface. Glossy surfaces should be sanded dull. All new masonry, concrete, cement and block surfaces must be cured for at least 3 weeks prior to painting. All surfaces should be dry before painting and free from cracks. New or porous surfaces should be primed with **EcoPrimer** or Sherwin-Williams® **Masonry Conditioner** before painting.

#### APPLICATION

**Thinning/Cleaning:** Tap water.

**Application tools:** Brush, Roller or Airless spray.

**Application Temperature:** Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use. For better results apply the first coat diluted up to 20% by volume and then apply at least two coats diluted up to 10% by volume.

**Cleaning of Tools:** Remove as much paint as possible from tools and clean immediately with water and detergent solution.

**PACKING:** 0.75L, 5L, 10L, 15L.

**COLOUR RANGE:** Please refer to **PERLOTEX MATT®** colour chart.

**STORAGE:** Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



## Health and Safety Measures

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or label.
- It contains a biocidal product. It contains 5-Chloro -2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

## WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

**Note:** The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.

