

	<b>WHITE SPIRIT</b>
	<b>Diluent</b>

#### Description

**WHITE SPIRIT** is a mixture of Hydrocarbons and Isoalkanes Cyclic Aromatics. It is used as a diluent for all kinds of alkyd paints, enamels, primers, varnishes, aluminium paints etc. It is also used for cleaning brushes or any other tools.

#### Technical Specifications

Density at 15°C	:	0,760 – 0,793 g/cm <sup>3</sup>
Viscosity	:	10-12" Ford cup No.4
Flash point	:	>23°C
Aromatics	:	15 – 25%
Benzene	:	Max. 100ppm
Sulphur	:	Max. 5ppm
Initial Boiling point	:	Min. 142°C
Dry Point	:	Max. 205°C

**PACKING:** 1L, 4L & 20L.

**COLOUR:** Colourless.

**STORAGE:** Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

#### Health and Safety Measures

- Keep out of the reach of children.
- Flammable liquid and vapour.
- Causes damage to organs through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.
- May cause drowsiness or dizziness.
- Toxic to aquatic life with long lasting effects.
- Explosive with or without contact with air.
- Keep away from heat / sparks / open flames / hot surfaces. No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Avoid release to the environment.
- Wear protective gloves/protective clothing/eye protection/ face protection.
- **IF SWALLOWED:** Immediately call a **POISON CENTRE** or doctor/physician and show the container or label.
- **IF INHALED:** remove victim to fresh air and keep at rest in a position comfortable for breathing.
- For more information please refer to Safety Data Sheet.

## WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

**Note:** *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*