



ROAD MARKING PAINT

Description

Road Marking Paint is suitable for traffic marking or painting asphalt or concrete surfaces. It is based on a thermoplastic acrylic resin, which provides elasticity and durability.

Technical Specifications

Vehicle type	:	Thermoplastic Acrylic
Specific Gravity	:	1.36±0.05
Weight solids	:	75±1%
Viscosity	:	6.7±0.3 Poise
Coverage (on a smooth surface)	:	7-10m ² /L / coat for wet thickness of 200µm
Dilution	:	For brush or roller: up to 10%, by volume For airless spray: up to 20%, by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 15 minutes for wet thickness of 200µm Recoat: After 1 hour, depending on weather conditions
Flash point	:	<60°C
European Union Limit for this product (Cat. A/i): 500g/l (2010). This product contains max 400g/l VOC		

Instructions for Use

SURFACE PREPARATION

Apply on clean, dry surfaces. Remove all surface contamination, e.g. dust, pebbles, oil stains or other contaminants. Previously painted surfaces are cleaned and any flaking paint is removed prior to painting. Road Marking Paint is ready for use, it can however be thinned with **Thinner 11/11** (Peletico's product), up to 10% by volume for brush or roller application and up to 20% by volume for airless spray application.

APPLICATION

Thinning/Cleaning: Thinner 11/11 (Peletico's product).

Application tools: Brush, Roller or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before and during use. Apply at least two coats.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with **Thinner 11/11** (Peletico's product).

PACKING: 1L, 4L & 20L.

COLOUR RANGE: White, Black, Yellow, Blue, Evergreen (P137), Brick Red (P123) and Pewter (P129). Please refer to **PELELAC®** Peletico's colour chart.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



Health and Safety Measures

- Keep out of reach of children.
- Highly flammable liquid and vapour.
- Causes skin irritation.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Wash thoroughly with soap and water after handling.
- Wear protective gloves / eye protection / face protection.
- IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
- If skin irritation occurs: Get medical advice / attention if you feel unwell and show the container or label.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.

