



A-10 QUICK DRYING INDUSTRIAL ENAMEL

Quick Drying Industrial Enamel Paint

Description

A quick drying industrial enamel with excellent durability, gloss and colour retention, suitable for primed steelwork with **A-10 Metal Primer**. It is recommended for machinery, primed steelwork and all types of metal structures.

Technical Specifications

Vehicle type	:	Styrene Modified Alkyd Resin
Specific Gravity	:	1.44±0.04
Weight solids	:	70±1%
Viscosity	:	130±10" Ford cup No.4
Gloss	:	>80 at 60° (Gloss) <15 at 60° (Matt)
Coverage	:	13-15m ² /L / coat
Dilution	:	For conventional or airless spray: up to 10% by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 5-10 minutes Recoat: After 12 hours depending on weather conditions
Flash point	:	<60°C
European Union Limit for this product (Cat. A/i): 500g/l (2010). This product contains max 490g/l VOC		

Instructions for Use

SURFACE PREPARATION

Remove all surface contamination, e.g. dust, oil stains, or other contaminants using **Thinner 11/11** (Peletico's product). Peeling or cracked paint should be scraped off and sanded to a sound surface. New metal surfaces should be primed with **A-10 Metal Primer** before applying **A-10 Quick Drying Industrial Enamel**. Apply a first coat of **A-10 Quick Drying Industrial Enamel** and after 5 minutes a final ample coat is applied crosswise.

APPLICATION

Thinning/Cleaning: The product is ready for use. It could be diluted, if needed, with **Thinner 11/11** (Peletico's product).

Application tools: Airless Spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before and during use.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with **Thinner 11/11** (Peletico's product).

PACKING: 1L, 2.5L, 4L & 20L.

COLOUR RANGE: White & Black. Available in gloss and matt.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

- Keep out of reach of children.
- Flammable liquid and vapour.
- Causes serious eye irritation.
- Causes skin irritation.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Wear protective gloves/eye protection/ face protection.
- IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
- If skin irritation occurs, get medical advice/ attention and show the container or label.
- Do not empty into drains.
- Avoid release to the environment.
- **Contains:** 2-BUTANONE OXIME. May produce an allergic reaction.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

***Note:** The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*