

	<b>MX3</b>
	<b>Fungicide Solution</b>

#### Description

Fungicide solution which eliminates, removes and prevents the development of fungi and other micro-organisms on interior and exterior surfaces. It can be applied on new or existing surfaces of brick, concrete, plaster, wood or on already painted surfaces.

#### Technical Characteristics

Vehicle Type	:	Water
Specific Gravity	:	1.00±0.01
Viscosity	:	10±1" Ford Cup No.4
Dilution	:	Ready to use

#### Instructions for Use

##### **SURFACE PREPARATION**

Surfaces should be free from dirt, dust, oil stains and dampness. On surfaces with mildew, fungus etc remove all loose residues before applying **MX3**. Spray over surface, avoiding over spraying. After 15 minutes wipe over using a cloth or sponge to remove the mould. In case the surface is not completely clean, repeat the procedure. When surface is dry it can be painted over. For more protection against future growth of mould and fungi, apply **Maxicote Fungicide Emulsion** (Peletico's product).

##### **APPLICATION**

**Thinning/Cleaning:** Ready for use.

**Application Temperature:** Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Shake well before use. During application wear a protective face mask and gloves.

**Cleaning of Tools:** In case a cloth or sponge is used during application, wash thoroughly with water and soap before disposal.

**PACKING:** 500ml.

**COLOUR:** Colourless.

**STORAGE:** Store in a dry place, away from direct sunlight and/or extreme temperatures. After use, twist trigger nozzle to "OFF" position.

## Health and Safety Measures

- Keep out of the reach of children.
- In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- In case of contact with the skin, wash immediately with plenty of water.
- If swallowed, seek medical advice immediately and show the container or the label.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

**Contains: Didecyldimethylammonium Chloride (DDAC) 0.5% (5g/l).**

## WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

**Note:** *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*