

		PAINT AND VARNISH REMOVER
Acid Free Paint and Varnish Remover		Acid Free Paint and Varnish Remover

Description

An acid free paint and varnish remover suitable to remove emulsion paints, alkyd paints, varnishes, acrylic textured finishes from wooden, plastered, metal and glass substrates. Does not contain Methylene Chloride.

Technical Specifications

Specific Gravity	:	0.95±0.02
Viscosity	:	95±5KU
Dilution	:	Ready for use
Flash point	:	<23°C
Coverage	:	3-5 m ² /L depending on the surface and the type of coating

Instructions for Use

APPLICATION

Apply a thin coat of **PAINT AND VARNISH REMOVER** on the surface. After a few minutes apply an abundant layer. After the product to be removed is soft enough, and before it dries out, scrape off with a paint scraper. On surfaces which are not smooth, use a hard brush. All surfaces, except wooden, are washed out with water and wiped dry. After drying, the surface can be painted. Wooden surfaces are preferably cleaned with white spirit. In such case, and if needed, light sanding is recommended before painting or varnishing the surface.

It is not recommended to use on plastic or rubber surfaces and other similar surfaces.

APPLICATION

Thinning/Cleaning: Ready for use.

Application tools: Brush, Paint Scraper, Hard Brush.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use. Open the container carefully!

PACKING: 0.5L, 1L & 4L.

COLOUR: Colourless.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



Health and Safety Measures

- Keep out of reach of children.
- Highly flammable liquid and vapour.
- May cause cancer.
- May cause genetic defects.
- May damage fertility. Suspected of damaging the unborn child. Restricted to professional users.
- Obtain special instructions, before use.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Use only in well ventilated areas.
- Wear protective gloves / eye protection / face protection.
- IF ON SKIN (or hair): take off immediately all contaminated clothing. Rinse skin with water / shower.
- IF EXPOSED OR CONCERNED: Get medical advice / attention and show the container or label.
- For more information please refer to Safety Data Sheet.

Contains: Naphtha (petroleum) hydrotreated heavy: Low boiling point hydrogen treated naphtha 1,2-Dimethoxyethane.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.





ISO

9001