



EMULSION STAINERS

Description

Concentrated emulsion stainers ideal for shading emulsion paints. They are recommended for shading light hues. Shading medium or dark hues is not recommended.

Technical Specificaons

Vehicle type	:	Va/VeoVa/Acrylic
Specific Gravity	:	1.20±0.05
Volume solids	:	36±3%
Weight solids	:	50±5%
Viscosity	:	110±2 KU's
Dilution	:	Not recommended
Flash point	:	Non-flammable

Instructions for Use

APPLICATION

Cleaning: Tap water.

Add to light hues emulsion paints until desired shade is achieved.

Stir well, in order to achieve uniform dispersion of the stainer, before application.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with water and detergent solution.

PACKING: 350gr.

COLOUR RANGE: Yellow Oxide, Fast blue, Fast Red, Fast Green, Fast Yellow, Black & Brown.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

Health and Safety Measures

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or the label.
- Contains a Biocidal product: Contains 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one(EC no.220-239-6)(3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*