



ProMar® MASONRY CONDITIONER

Clear Wall Primer with Strong Adhesion

Description

Clear Wall Primer which penetrates and revitalizes porous, chalking and friable interior and exterior building surfaces. It exhibits a high degree of penetration into the substrate. It provides an easy and quick wall surface treatment prior to decoration. It can be applied on concrete, plaster, wall levelled surfaces, concrete blocks, weathered old paint etc.

Technical Specifications

| | | |
|--|---|---|
| Vehicle type | : | Soya Bean Oil |
| Specific Gravity | : | 0.82±0.01 |
| Weight solids | : | 25±1% |
| Viscosity | : | 10±1" |
| Coverage (on a smooth surface) | : | 5-8m ² /L / coat |
| Dilution | : | Not Recommended |
| Drying time at 25°C and relative humidity 50% | : | Touch dry: 2-3 hours Second Coat: 12 hours Final decoration: 24 hours |
| Flash point | : | >60°C |
| EU limit value for this product (cat. A/h): 750g/l (2010). This product contains max 730g/l VOC | | |

Instructions for Use

SURFACE PREPARATION

All surfaces must be clean, dry and free of grease, oil & other contaminants. All new concrete surfaces must be cured for at least three weeks prior to the application of **ProMar® MASONRY CONDITIONER**.

APPLICATION

Application tools: Brush, Roller, Conventional or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Generally, one coat is sufficient. However, extremely porous or friable surfaces may require a second coat. Apply only sufficient quantity as will be absorbed by the substrate, without forming a visible glaze on the surface. Application is not recommended if rain is expected in the next 12 hours.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with white spirit.

PACKING: 1L, 4L, 20L.

COLOUR: Transparent.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the can after application.

Health and Safety Measures

- Keep out of reach of children.
- Flammable liquid and vapour
- Causes damage to organs through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.
- May cause drowsiness or dizziness
- Toxic to aquatic life with long lasting effects.
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Wear protective gloves/eye protection/face protection.
- IF INHALED: remove person to fresh air and keep them in a comfortable breathing position.
- IF SWALLOWED: Immediately call Poison Centre or doctor and show the container or label.
- For more information please refer to Safety Data Sheet.

Contains: white spirit.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note 1: The Sherwin-Williams® product range is manufactured in Cyprus by Peletico Ltd, under licence from the Sherwin-Williams® Company, Cleveland, Ohio USA, owner of the Registered* Trademarks.

Note 2: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.