



## PREPRITE® 200

White, Acrylic Wall Primer

### Description

A premium quality, water based, white wall primer, for interior surfaces. It can be applied on plaster, drywall (as a sealer), masonry or previously painted surfaces. It has excellent hiding and coverage properties, covering dark colours and facilitating dramatic topcoat colour changes. It is particularly used to enhance the appearance of bright colours with low hiding power, as recommended on the Sherwin-Williams® fan deck.

### Technical Specifications

Vehicle type	:	Va/VeoVa/Acrylic
Specific Gravity	:	1.26±0.02
Volume solids	:	34±1%
Weight solids	:	41±1%
Viscosity	:	95±5KU's
Gloss	:	<5 at 85° Matt (EN13300)
Coverage (on smooth surface)	:	9-11m <sup>2</sup> /L / coat
Dilution	:	Not recommended
Drying time at 25°C and relative humidity 50%	:	Touch dry: 1-2 hours Recoat: 4 hours depending on weather conditions
Flash point	:	Non-flammable
<b>EU limit value for this product (cat. A/a): 30g/l (2010). This product contains max 15g/l VOC</b>		

### Instructions for Use

#### SURFACE PREPARATION

Clean surface before priming, if needed remove any oil stains or other dirt by washing with an appropriate cleaner, rinse and allow to dry. Peeling paint is scraped off prior to priming. All new masonry, concrete, cement and block surfaces must be cured for at least three weeks prior to priming.

#### APPLICATION

**Application tools:** Brush, roller or airless spray.

**Application Temperature:** Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use.

**Cleaning of Tools:** Remove as much paint as possible from tools and clean immediately with water and detergent solution.

**PACKING:** 1L, 4L, 20L.

**COLOUR RANGE:** Please refer to **Sherwin-Williams®** fan deck.

**STORAGE:** Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

## Health and Safety Measures

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or label.
- It contains a biocidal product. It contains 5-Chloro-2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

### WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

**Note 1:** The Sherwin-Williams® product range is manufactured in Cyprus by Peletico Ltd, under licence from the Sherwin-Williams® Company, Cleveland, Ohio USA, owner of the Registered\* Trademarks.

**Note 2:** The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.