

	<h2>ECOPRIMER</h2> <p>Clear, Odourless, Penetrative, Acrylic Stabiliser</p>
---	--

Description

A water based, micronized primer/stabiliser for interior and exterior surfaces. It is colourless, odourless and exhibits high penetration in porous or lightly chalked building surfaces. It will stabilise surfaces, previously painted with old distempers or similar products.

Technical Specifications

Vehicle type	:	Acrylic
Specific Gravity	:	0.99 ±0.02
Volume solids	:	14±0.2%
Weight solids	:	15±0.2%
Viscosity	:	11±1" Ford Cup No:4
Gloss	:	N/A
Coverage (on a smooth surface)	:	8-11m ² /L / coat
Dilution	:	Not recommended
Drying time at 25°C and relative humidity 50%	:	Touch dry: 1 hour Recoat: 3 hours depending on weather conditions
Flash point	:	Non-flammable
EU limit value for this product (cat. A/h): 30g/l (2010). This product contains max 5g/l VOC		

Instructions for Use

SURFACE PREPARATION

Clean surface before priming, if needed remove any oil stains or other dirt by washing with an appropriate cleaner, rinse and allow drying. Peeling paint is scraped off prior to priming. All new masonry, concrete, cement and block surfaces must be cured for at least three weeks prior to priming.

APPLICATION

Cleaning: Tap water.

Thinning: Not recommended.

Application tools: Brush, Roller, Conventional or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Cleaning of Tools: Remove as much product as possible from tools and clean immediately with water and detergent solution.

PACKING: 1L, 4L, 20L.

COLOUR: Colourless.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



Health and Safety Measures

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or label.
- It contains a biocidal product. It contains 5-Chloro -2-methyl-4-isothiazolin-3-one (EC no. 247- 500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.

