



## WOOD PRIMER

### Water Based Wood Primer

#### Description

A water-based Wood Primer, based for interior and exterior surfaces. It can be applied on wooden surfaces, MDF etc. It exhibits high hiding power, excellent adhesion and knot blocking. It stops wood resins staining through. It is ideal primer for water-based enamels in order to get higher covering and endurance.

#### Technical Specifications

Vehicle type	:	Acrylic
Specific Gravity	:	1.44±0.03
Volume solids	:	39±1%
Weight solids	:	56±1%
Viscosity	:	105±5KU's
Gloss	:	<5 at 60°, MATT (EN13300)
Coverage (on a smooth surface)	:	9-12m <sup>2</sup> /L / coat
Dilution	:	For brush or roller 5-10%, by volume For Airless spray up to 20%, by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 1/2 hour Recoat: 1-2 hours depending on weather conditions
Flash point	:	Non-flammable
<b>EU limit value for this product (cat. A/d): 130g/l (2010). This product contains max 5g/l VOC</b>		

#### Instructions for Use

##### SURFACE PREPARATION

Remove all surface contamination, e.g. dust, oil stains and dampness by washing with an appropriate cleaner, rinse thoroughly and allow drying. For better results, moisture content of wood is recommended to be between 15-20%. Peeling or cracked paint should be scraped off and sanded to a sound surface. Wood Primer should be applied prior to Undercoat.

##### APPLICATION

**Thinning/Cleaning:** De-ionized water.

**Application tools:** Brush, Roller, Conventional or Airless spray.

**Application Temperature:** Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use.

**Cleaning of Tools:** Remove as much paint as possible from tools and clean immediately with water and detergent solution.

**PACKING:** 0.5L 1L, 2.5L, 4L.

**COLOUR:** White.

**STORAGE:** Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

**Health  
and Safety  
Measures**

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or the label.
- It contains a biocidal product. It contains 5-Chloro -2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

**WASTE MANAGEMENT**

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

***Note:** The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*