



ALKALI RESISTING PRIMER

Description

Solvent based Alkali Resisting Primer for interior surfaces exhibiting high PH (up to 12). It seals surfaces against salt exudation, stains due to smoke, oils etc. The surface can then be coated with emulsion paints.

Technical Specifications

Vehicle type	:	PU Modified Soya Bean Oil
Specific Gravity	:	1.35±0.04
Weight solids	:	74.5±1%
Viscosity	:	4 – 5 Poise
Coverage (on a smooth surface)	:	8-12m ² /L / coat
Dilution	:	For brush or roller: up to 10% by volume For airless spray: up to 20%, by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 5-6 hours Recoat: After 24 hours, depending on weather conditions
Flash point	:	<61°C
European Union Limit for this product (Cat. A/g): 350g/l (2010). This product contains max 350g/l VOC		

Instructions for Use

SURFACE PREPARATION

Remove all surface contamination, e.g. soot, dust, salt exudation, oil stains and dampness by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Peeling or cracked paint should be scraped off and sanded to a sound surface. In case of fire in a building, the walls are cleaned first and then painted with Alkali Resisting Primer, to seal in, any soot stains.

APPLICATION

Thinning/Cleaning: White Spirit.

Application tools: Brush, Roller, Conventional or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use and apply in two coats by brush, roller or airless spray. Painted surfaces can be washed / cleaned after 30 days.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with White Spirit.

PACKING: 1L, 2.5L & 4L.

COLOUR RANGE: White.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

Health and Safety Measures

- Keep out of the reach of children.
- Causes damage to organs through prolonged or repeated exposure.
- Harmful to aquatic life with long lasting effects.
- Wash with water and soap thoroughly after handling.
- Avoid release to the environment.
- Get medical advice/attention if you feel unwell and show the container or label.
- For more information please refer to Safety Data Sheet.

Contains: 2-BUTANONE OXIME / DIPENTENE. May produce an allergic reaction.

Contains: NAPHTHA (PETROL) HYDRODESULFURIZED HEAVY, WHITE SPIRIT.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.