



H&C® COLORTOP™

Water-Based Solid Colour Concrete Stain

Description

A water-based concrete stain that provides a long-lasting, durable and decorative finish to interior or exterior concrete, masonry, or asphalt surfaces. It can be applied on walkways, patios, pool decks, basement floors, and block and stucco walls. It is highly resistant to pool chemicals and many other household chemicals for long lasting beauty and protection. Its water-based formulation allows for easier application and clean-up.

Technical Specifications

Vehicle type	:	100% Acrylic
Specific Gravity	:	1.2±0.02
Volume solids	:	30±2%
Weight solids	:	43±2%
Viscosity	:	108±2KU's
Gloss	:	Low Lustre <35
Coverage (on a smooth surface)	:	3-7m²/L/ coat, depending on the substrate
Dilution	:	Not Recommended
Drying time at 25°C and relative humidity 50%	:	Touch dry: 30 minutes Light Traffic and Recoat: 2 hours Heavy traffic: 72-96 hours Full Cure: 7-14 days
Flash point	:	260 °C
EU limit value for this product (cat. A/i): 140g/l (2010). This product contains max 140g/l VOC		

Instructions for Use

SURFACE PREPARATION

All surfaces must be clean, dry and free from grease, oil, or other contamination. Dirty surfaces are cleaned with a suitable detergent, washed with clean water, and left to dry at least 24 hours before staining. If surface has been previously painted, remove all old, peeling, flaking paint by rough sanding to ensure adhesion of **H&C® COLORTOP™**. Allow new concrete surfaces to cure at least 28 days. Prepared concrete must have a pH of 6 to 10.

APPLICATION

Application tools: Brush, Roller, Conventional or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir product thoroughly before and during application. A minimum of two coats are required. For best coverage, apply the second coat perpendicular to the first coat. Extremely porous surfaces may require a third coat for a uniform appearance.

Do not apply **H&C® COLORTOP™ CONCRETE STAIN** if rain is expected within 12 hours following application.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with warm water and soap.



PACKING: 3.78L, 18.92L.

COLOUR RANGE: Please refer to **Sherwin-Williams®** colour card.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the can after application.

**Health
and Safety
Measures**

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or the label.
- Apply only in well ventilated areas.
- Do not empty into the drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus paint into the drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note 1: The product is imported in Cyprus by Peletico Ltd, from the Sherwin-Williams® Company, Cleveland, Ohio USA, owner of the Registered* Trademarks.

Note 2: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.