



OIL VARNISH STAIN

Alkyd Varnish

Description

An alkyd transparent varnish, providing high wear resistance and durability. It protects and preserves the life span of soft interior wooden surfaces.

Technical Specifications

Vehicle type	:	Alkyd Resin
Specific Gravity	:	0.90±0.01
Weight solids	:	53±2%
Viscosity	:	100±10" Ford cup No.4
Coverage (on a smooth surface)	:	10-12 m ² /L / coat
Dilution	:	Up to 10% by volume
Drying time at 25°C and relative humidity 50%	:	Touch dry: 6 hours Recoat: 24 hours depending on weather conditions
Flash point	:	>61°C
European Union Limit for this product (Cat. A/e): 400g/l (2010). This product contains max 225g/l VOC		

Instructions for Use

SURFACE PREPARATION

Surfaces should be free from dirt, dust, oil stains and dampness. Peeling or cracked varnish, should be scraped off and sanded to a sound surface. Glossy surfaces should be sanded dull.

APPLICATION

Thinning/Cleaning: White Spirit.

Application tools: Brush.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use. It is recommended to apply 3 coats. Apply evenly using light strokes following the grain of the wood. Light sanding and cleaning is recommended between the subsequent coats.

Cleaning of Tools: Remove as much product as possible from tools and clean immediately with white spirit.

PACKING: 025L, 0.5L, 1L and 2.5L.

COLOUR RANGE: Clear, Oak, Walnut and Cherry Red. Please refer to **OIL VARNISH STAIN** colour card.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.



Health and Safety Measures

- Keep out of reach of children.
- Causes damage to organs, through prolonged or repeated exposure.
- May cause drowsiness or dizziness.
- Toxic to aquatic life with long lasting effects.
- Wash with water and soap thoroughly after handling.
- Avoid release to the environment.
- Store in a well-ventilated place.
- Keep container tightly closed.
- **IF INHALED:** Remove person to fresh air and keep comfortable for breathing.
- Call a **POISON CENTER**/doctor if you feel unwell and show the container or label.
- **Contains: 2-BUTANONE OXIME.** May produce an allergic reaction.
- For more information please refer to Safety Data Sheet.

Contains: WHITE SPIRIT.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

***Note:** The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*

