



TEAK OIL

Teak Oil that Protects and Maintains Hard Wood

Description

A special processed oil, suitable for use on teak or other similar types of hard wood for interior and exterior surfaces. It revives the natural colour and texture of wood which has been worn out due to weather or other conditions. It is easy to apply and has good coverage.

Technical Specifications

Vehicle type	:	Alkyd Resin
Specific Gravity	:	0.89±0.02
Weight solids	:	30±1%
Viscosity	:	15±1" Ford cup No.4
Coverage	:	Depends on the absorption of surface
Dilution	:	Up to 5%, by volume (if required)
Drying time at 25°C and relative humidity 50%	:	Touch dry: 6 hours Recoat: After 24 hours depending on weather conditions
Flash point	:	<40°C
European Union Limit for this product (Cat. A/i): 500g/l (2010). This product contains max 490g/l VOC		

Instructions for Use

SURFACE PREPARATION

Surfaces should be free from dirt, dust, oil stains and dampness. Peeling or cracked varnish, should be scraped off and sanded to a sound surface.

APPLICATION

Thinning/Cleaning: White Spirit.

Application tools: Brush or lint free cloth.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use. **TEAK OIL** is only used on dry and clean surfaces. Apply a thin layer following the grain of the wood. After 5 minutes, wipe off any excess oil with a lint free cloth. To get the best protection apply 3 coats, leaving 24 hours between coats. It is recommended to apply **TEAK OIL** once or twice a year depending on the wear/condition of the wood.

Cleaning of Tools: Remove as much product as possible from tools and clean immediately with white spirit. In case a cloth is used during application, wash thoroughly with water and soap before disposal.

PACKING: 1L and 4L.

COLOUR: Colourless .

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

- Keep out of reach of children.
- Flammable liquid and vapour.
- Causes damage to organs, through prolonged or repeated exposure.
- May be fatal if swallowed and enters airways.
- Causes serious eye irritation.
- Causes skin irritation.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.
- Toxic to aquatic life with long lasting effects.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Wear protective gloves / eye protection / face protection.
- **IF SWALLOWED:** Immediately call a poison centre / doctor and show the container or label.
- **IF INHALED:** Remove person to fresh air and keep comfortable for breathing.
- For more information please refer to Safety Data Sheet.

**Contains: WHITE SPIRIT
1,2,4-TRIMETHYLBENZENE.**

WASTE MANAGEMENT

Do not empty surplus product into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: *The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.*