

	<h2 data-bbox="359 235 518 280">SPATULIN</h2> <h3 data-bbox="359 380 526 414">Acrylic Putty</h3>
---	--

Description

A ready to use, general purpose acrylic putty for interior and exterior surfaces. It is suitable for use on wood, cement based plasters and gypsum boards. It is quick drying, easy to apply with excellent filling and sanding properties, leaving a smooth and durable surface.

Technical Specifications

Vehicle type	:	100% Acrylic
Weight solids	:	74±1%
Viscosity	:	245±45 Poise
Dilution	:	Ready for use
Drying time at 25°C and relative humidity 50%	:	Touch dry: 1 hour depending on weather conditions and the thickness of coat. For deep cracks (>0.5mm) allow the first layer to dry for 12 hours, before applying a second layer
Flash point	:	Non-flammable

Instructions for Use

SURFACE PREPARATION

All surfaces should be clean, free of dust, oil, residues of other building materials, etc. before applying the product.

It is ready to use. Can be applied with paint scrapper or spatula. Before decorating, the final surface should be made smooth using fine sandpaper. After sanding, surface should be primed with Peletico's **ECO PRIMER** or any other primer depending on the substrate.

APPLICATION

Thinning/Cleaning: Tap water. Thinning is not recommended.

Application tools: Spatula or paint scrapper.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Stir well before use.

Cleaning of Tools: Clean tools immediately with hot water and soap.

PACKING: 0.4kg, 1kg, 5kg

COLOUR: Off white.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

Health and Safety Measures

- Keep out of reach of children.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed, seek medical advice immediately and show the container or label.
- It contains a biocidal product. It contains 5-Chloro-2-methyl-4-isothiazolin-3-one (EC no. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no. 220-239-6) (3:1). May produce an allergic reaction.
- Apply only in well ventilated areas.
- Do not empty into drains.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

WASTE MANAGEMENT

Do not empty surplus product into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.