



STONE & CONCRETE SEALER

Acrylic Floor & Wall Sealer

Description

Clear acrylic floor and wall sealer for interior and exterior surfaces. It can be applied on surfaces of stone (natural and artificial), concrete, terrazzo tiles, terracotta. It seals pores (prevents immediate absorption of liquids), prevents spalling and pitting, provides excellent resistance to stains, prevents efflorescence and resists yellowing. It can be applied on both horizontal and vertical surfaces (floors & walls). It is available in Gloss and Semi-matt.

Technical Specifications

Vehicle type	:	100% Acrylic
Specific Gravity	:	Gloss: 0.83±0.02 Semi-matt: 0.82±0.02
Volume solids	:	N/A
Weight solids	:	Gloss: 26±1% Semi-matt: 15±1%
Viscosity	:	Gloss: 22.5±2.5" Semi-matt: 12.5±2.5"
Gloss	:	N/A
Coverage (on a smooth surface)	:	8-12m ² /L/ coat
Dilution	:	Not recommended
Drying time at 25°C and relative humidity 50%	:	Touch dry: 3-4 hours Recoat: 24 hours Light traffic: 24 hours Normal traffic: 72 hours
Flash point	:	>60° C
EU limit value for this product (cat. A/h): 750g/l (2010). This product contains max 725g/l VOC		

Instructions for Use

SURFACE PREPARATION

All surfaces must be clean, dry and free of grease, oil and other contaminants. All new concrete surfaces must be cured for at least three weeks prior to application. Repair any cracks and then sand to a sound surface.

APPLICATION

Application tools: Brush, Roller, Conventional or Airless spray.

Application Temperature: Ideal temperature for the application should be between 5-35°C and the relative humidity should not exceed 80%.

Depending on the porosity of the substrate, more than one coat may be required to obtain complete penetration and sealing.

Do not apply if rain is expected within 12 hours from time of application.

Cleaning of Tools: Remove as much paint as possible from tools and clean immediately with white spirit.

PACKING: 1L, 4L, 20L.

COLOUR RANGE: Transparent.

STORAGE: Store in a dry place, away from direct sunlight and/or extreme temperatures. Close the container after application.

Health and Safety Measures

- Keep out of reach of children.
- Flammable liquid and vapour.
- Causes damage to organs through prolonged or repeated exposure.
- May cause drowsiness or dizziness.
- May be fatal if swallowed and enters airways.
- Toxic to aquatic life with long lasting effects.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
- Keep container tightly closed.
- Wash with water and soap thoroughly after handling.
- Wear protective gloves/eye protection/face protection.
- IF INHALED: remove person to fresh air and keep them in a comfortable breathing position.
- IF SWALLOWED: Immediately call Poison Centre or doctor and show the container or label.
- Do not induce vomiting.
- In case of fire: use dry powder extinguisher to extinguish.
- Avoid release to the environment.
- For more information please refer to Safety Data Sheet.

Contains NAPHTHA (PETROL.) HYDRODESULFURIZED HEAVY WHITE SPIRIT.

WASTE MANAGEMENT

Do not empty surplus paint into drains, and do not dispose together with household refuse. Advice regarding disposal and collection should be sought from the local authorities.

Note 1: The Sherwin-Williams® product range is manufactured in Cyprus by Peletico Ltd, under licence from the Sherwin-Williams® Company, Cleveland, Ohio USA, owner of the Registered* Trademarks.

Note 2: The information supplied in our literature or given by our employees, agents or distributors concerning the use of our products is based upon extensive experience and given in good faith in order to help you. We guarantee the consistent high quality of our products; however, as we have no control over site conditions of the executions of work, we cannot accept any liability for any loss or damage, which may arise as a result thereof.